

1. Description

The Everlux adhesive is easy to apply, fast, clean and flexible, with excellent mechanical properties inside and out. Without solvents or silicone. Strong adhesion on most surfaces, even more uneven. Resistant to UV and temperature variations.

2. Technical characteristics

Aspect:	Pasty.
Colour:	White.
Stretching:	Acetic acid
Maximum resistance:	High fluidity that allows easy application (extrusion).
Time to form a film:	35-45 minutes
Density:	1.5
Bonding time:	5 minutes
Temperature of application:	+5°C to +40°C
Resistance to temperature:	-40 °C to +90 °C

3. Directions to use

- The signs and the surfaces where they are going to be applied must be dry and with no dust, oil or grease. Use a cloth moistened with alcohol to clean the surface of the sign and the installation surface.
- Apply the Everlux adhesive using a manual or pneumatic pistol.
- Apply a 5mm continuous string of the adhesive in the shape of an N across the back of the sign to be glued; Apply the sign on the surface to be installed, exerting a strong pressure; It is possible to reposition the sign within the first 5 minutes after gluing.

4. Packaging and spread

Cartridge of 290 ml.

Considering a line of 5mm in diameter and 15m linear: 29 signs (15x15cm), 19 signs (30x15cm), 12 signs (40x30 cm).:

5. Storage and time it lasts

Store between +5 °C and +25 °C in a dry and fresh place.

To be used within 18 months after the manufacturing date of production indicated on the package. After that date, the adhesive retains all its properties provided that it is in tamped packaging and under the indicated storage conditions.

6. Hygiene and Safety

Apply the product in well-ventilated areas. In case of contact of the product not cured with skin or eyes, wash the affected area with water and seek medical advice.

For further information, please consult the relative Safety Data Sheet.